


### Anchor slings

<b>Certifications</b>	EN 354-Connecting lanyards EN 566-Mountaineering equipment EN 795-Anchor devices (slings) <b>CE 2756</b>
<b>Webbing</b>	Type: tubular webbing; Width: 26 mm; Material: PES fibers;
<b>Breaking strength</b>	Minimum <b>30 kN</b>
<b>Length</b>	60 – 200 cm <i>*other lengths on request</i>



<b>LISO</b>	<b>Black Art. No.</b>	<b>Yellow Art. No.</b>	<b>Red Art. No.</b>
60 cm	12-4030-95-06-00	12-4030-29-06-00	12-4030-44-06-00
80 cm	12-4030-95-08-00	12-4030-29-08-00	12-4030-44-08-00
100 cm	12-4030-95-10-00	12-4030-29-10-00	12-4030-44-10-00
120 cm	12-4030-95-12-00	12-4030-29-12-00	12-4030-44-12-00
160 cm	12-4030-95-16-00	12-4030-29-16-00	12-4030-44-16-00
200 cm	12-4030-95-20-00	12-4030-29-20-00	12-4030-44-20-00



<b>LISO S</b>	<b>Black Art. No.</b>	<b>Yellow Art. No.</b>	<b>Red Art. No.</b>
60 cm	12-4230-95-06-00	12-4230-29-06-00	12-4230-44-06-00
80 cm	12-4230-95-08-00	12-4230-29-08-00	12-4230-44-08-00
100 cm	12-4230-95-10-00	12-4230-29-10-00	12-4230-44-10-00
120 cm	12-4230-95-12-00	12-4230-29-12-00	12-4230-44-12-00
160 cm	12-4230-95-16-00	12-4230-29-16-00	12-4230-44-16-00
200 cm	12-4230-95-20-00	12-4230-29-20-00	12-4230-44-20-00